

CLEANING FILTER MEDIA

USING FILTER CLEANER

Using Filter Cleaner is effective in removing scale, rust, cosmetics, oils, etc. which commonly reduce the performance of sand, DE and cartridge filters. The dry, granular form makes it easy to use with greater handling safety.

Precautions: DO NOT let the pump run dry. DO NOT backwash the solution into the pool, over grass or desirable plants.

PREPARATION

- Backwash the filter normally.
- Leave handle in backwash position.
- Shut off the pump.
- Remove pump hair and lint pot cover.
- Remove filter drain plug.
- Allow water to drain from filter.
- Replace the filter drain plug securely.

APPLICATION OF THE CLEANER

Fill a plastic pail with warm tap water.

Add 500 g of filter cleaner into 20L of lukewarm water while stirring with a wooden stick (the solution will dissolve and turn red).

For Cartridge Filters:

Remove cartridges and elements and soak overnight in a plastic pail.

After soaking, rinse thoroughly and replace them in the filter.

For Sand Filters: (Or if elements cannot be removed)

Add Filter Cleaner solution directly into the filter tank.

Use sufficient solution to cover the sand or elements.

Let stand over night.

Drain, then backwash to thoroughly rinse sand and elements.

RESUME NORMAL FILTER OPERATION

Prime the pump and backwash for 6 minutes or until the water coming out of the backwash line is clear.

Note:

Do not allow the solution to get into the pool.

Shut off the power to the pump, put handle in filter position and then restart the pump.